

The mechanisms of water are unbearably complex. A tension is created between the resistance of stone and the erosional power of water. This shape that remains — a long, narrow mansion full of dark walkways and parlors — is a geomorphological search for resolution. I am here seeking resolution as well. I struggle to find a balance between darkness and hope...

It is hard to make sense of it because I live in a human world where things are labeled either good or bad. That this canyon and its floods are neither does not sit will with this way of thinking.

The Desert Cries – A Season of Flash Flood in a Dry Land (p. 95) / Craig Childs









Existing County Programs

USGS East Mountain Program

(\$100 K / 50 percent Share)


- Precipitation Stations (8)/ Surface Flow Monitoring (3 stations)
- Water Level Monitoring Program (23 wells)
- Spring Chloride / Isotope Monitoring (5 sites)
- Interpretive Reports / Peer Review
- Possible Additional Programs
 - Wastewater System Recharge
 - Quantitative Recharge Evaluation

Existing County Programs

- Bernalillo County Groundwater Monitoring Program
 - Annual Sampling (18 monitoring wells plus County facilities)
 - Water Level Monitoring (36 Locations County Wide)
 - Monitoring Well Acquisition / Drilling (2 wells, 4 possible sites)
 - Spring flow monitoring (County Open Space at Carlito and Ojito)
 - Landfill Sampling
 - Bernalillo County Regional Groundwater Sampling Report
- Ad hoc committees / Planning
 - OSE / Entranosa Hydrologic Committee
 - East Mountain Area Plan / West Tijeras Plan / Public Outreach
 - Regulatory, Ordinance, Criteria Reviews
- Estancia Basin Water Planning Committee
- ISC Regional Water Planning Advisory Counil
- Subdivision Review / Water Conservation Ordinance




Classic Hydrologic Cycle






Groundwater Flow - Basics







WATER BUDGET

15% RUNOFF

80% EVAPORATION

5% RECHARGE


(VARIABLE)




Evapotranspiraton



Geologic Complexities









BALLEALIC DOLLANWATED INC

EMA ANNUAL RECHARGE ESTIMATES

	Annual Precipitation	Recharge			
Area	(acre - feet)	3 percent	7.5 percent	15 percent	
West Facing Slopes of the Sandias	14,200	426	1,065	2,130	
West Facing Slopes of the Manzanos	60,700	1,821	4,553	9,105	
Estancia Basin Portion of EMA	88,800	2,664	6,660	13,320	
Tijeras Canyon	64,200	1,926	4,815	9,630	
San Pedro Creek	44,700	1,341	3,353	6,705	
Total for EMA Area	197,700	5,931	14,828	29,655	



EMA ESTIMATED RECHARGE

Table 5. Median, minimum, maximum, and range of percent recharge at selected springs estimated by using the chloride mass balance technique.

[Site locations shown in fig. 1. Abbreviations: mg/L, milligram per liter; in, inches]

			Chloride concentration (mg/L)			Estimated annual recharge (in)			
Site number	Spring name	Number of samples	Median	Minimum	Maximum	Median	Minimum	Maximum	Percent recharge range (percent)
45	Wolf	11	32.6	4.33	41.5	0.2	0.2	1.5	0.70 - 6.9
46	Carlito	13	1.69	1.61	1.94	3.9	3.4	4.1	15 - 19
47	Canoncito	11	1.59	1.31	1.73	4.2	3.8	5.0	17 - 23
48	Cole	11	2.07	1.88	2.29	3.2	2.9	3.5	13 - 16
49	Cienega	12	15.9	2.43	20.7	0.4	0.3	2.7	1.4 - 12

Scientific Investigations Report 2008–5179



EMA ANNUAL RECHARGE ESTIMATES

- 37,400 af (Maxey-Eakin / entire area/ EMA Plan)
- 29,655 af (15 percent assumed, no west slopes)
- 9,788 af (Elev. Adj. / no west slope / EMA Plan)
- 5,931 af (3 percent assumed, no west slopes)
- Average Value: 20,932 acre-feet.

ESTIMATED EMA ANNUAL USE (ac-ft)


```
Spring Flows (Best Guess )
                                             851?
EMA Utility System Usage
  NE Small Systems (30):
                                             249 >
  SE Small Systems (9)
                                              62 >
  Entranosa (existing pumpage)
                                            1,200 >
  Entranosa (outstanding commitments) <
                                            1,000 >
Domestic Wells
      NE and SE (4,300 x 0.3)
                                             1,290 >
```

Balance

5,350 (rough guess maximum)




Water Levels in Sandia Park Well 1









Water Levels in Pinon Ridge Well 1





























But my well?

- Was fine until ... (casuality vs. cause)
- Makes "x" gpm (rate vs capacity)
- Is ___, but my neighbor's is ____


Individual Well Hydraulics








Well Densities





Effect of Domestic Well Pumping





Considerations During Construction

- Well Hydraulics / Pump and Well Maintenance Problems
- Localized Pumping / Well Density
- Geologic Complexities
- Effects of Drought
- Regional Water Level Trends

So What Can I Do?

- Conserve, Conserve
- Keep your well and septic tank in good operating conditions
- Practice Green (Energy = Water)
- Know about your well water levels, depth, capacity
- Be Active in Community Planning

Bernalillo County Contacts

- Bernalillo County Public Works 848-1500
 - Program Manager: Mary Murnane
 - Water Resources: Dan McGregor
 - Water Conservation: Kerry Bassore
- Water Waste Hotline

224-2100

Bernalillo County Env. Health

314-0310



<u>Existing County Ordinance – Minor Subdivisions, Sec 74-97</u>

Handled through BCEH Review

- One well log from within one mile in representative geologic conditions
- Statement of "estimated yield in gpm"
- "Where certain geologic conditions exist…"
- No requirements for
 - Impact on neighboring wells
 - No minimum spacing requirements
 - "First in time" rights protection (misconception)
 - Detailed hydrogeologic reports



Existing County Ordinance – Major Subdivisions, Sec 74-96

Handled through BCPW Review

- Community Supply (20 lots or more)
 - Letter of Availability
 - Name of Utility
 - "Ready, willing, and able to provide 0.6 ac-ft per lot"
 - "At the discretion of the County"
- Individual or Shared Well Supplies
 - Hydrogeologic Report
 - » 70 years supply, as designed or proposed
 - » Exploratory Wells
 - » Impact to others go dry, 50 percent, average decline of 1 foot per year or more
 - » Lowest Practical Pumping Level
- Proof of valid water right for Final Plat Approval

